

Grainger



Grainger - производит товары высокого качества, и имеет безупречную репутацию . Благодаря тому, что наша компания напрямую сотрудничает с фирмой-производителем, Вы сможете быстро получить товар по самой низкой цене. Если нужного товара, нет в списке, сообщите нам, и мы поможем Вам его найти.

ТОВАРЫ БРЕНДА

Продукт	Описание
10D457	
10E752	
10M819	Yellow Jacket Sniffer
11G076	PRESSURE REGULATOR,11G076, GRAINGER PRESSURE REGULATOR, MACHINED BODY OF CONSTRUCTION PVC,PRESSURE REGULATION (PSI)10 TO 125 INLET/OUTLET 2 IN. X 2 IN.,FNPT CONNECTION,MAX. WATER PRESSURE (PSI) 150, MAX. TEMP. (F) 140DEGREES ,SEAL VITON
11X260	
12850	
12T581	
14C127 10M	
1766LB	STEEL STRAPPING;WIDTH : 3/4IN ,THICKNESS : 0.020IN,LENGTH : 300 FT,PACKAGE DATA : CARTON PAC,SPECIFICATION : STANDARD DUTY, BREAKING STRENGTH 1765 LB, WIND RW
19XY44	
1ARV6	
1AVR4	
1DLZ2	
1DLZ3	
1DLZ4	
1DMD1	
1DMD2	
1DXL6	
1EJZ2	Magnetic Parts Tray
1EKB1	
1EKD1	
1JY33	
1KY16	
1LBE6	
1LMY2	(Flexible Metal Hose,Dia 1 1/2 In Manufacturer No.: G150FXFL120 Origin: US Harm Code: 8307103000 Hazardous Material: N ECCN:EAR99 NAFTA Qualified: Y)
1LMY6	(Flexible Metal Hose,Dia 2 In Manufacturer No.: G200FXFL120 Origin: US Harm Code: 8307103000 Hazardous Material: N ECCN:EAR99 NAFTA Qualified: Y)
1LY64	
1MUE8	
1NB50 ALTERNATIVE	

Продукт	Описание
1NU46	
1NY95	
1P894	
1R424A PARTS KIT	PART KIT, AIR FILTER
1RXJ7	WAFER CHECK, DOUBLE DISC, 2 IN, FLANGE, IRON GNG 4.00 Units MODEL: 0200-125WTIBB-T, ITEM: DOUBLE DISC CHECKVALVE, TYPE: DOUBLE DISC, SIZE: 2", CONNECTION: 125 CLASS WAFER FLANGE, LENGTH: 4-1/8", WIDTH: 2-1/8", OVERALL HEIGHT: 4-1/8", RATED FOR: 200 PSI, SEAT MATERIAL: BUNA N, SEAL: BUNA N, MATERIAL OF CONSTRUCTION: CAST IRON, MAX TEMP: 250 OF, STANDARDS FM APPROVAL AND API 598
1TAJ3	HOIST, LEVER CHAIN, 1TAJ3, GRAINGER LEVER CHAIN HOIST, 1 TON LOAD CAPACITY, 10 FT. LIFT, HOOK THROAT OPENING 1-3/32 IN, PULL TO LIFT RATED LOAD 72 LBS., MIN BETWEEN HOOKS 11-13/16 IN, LEVER LENGTH 9-5/8 IN, CHAIN LENGTH 11 FT., WESTON STYLE LOAD BRAKE, STANDARDS ANSI/ASME B30.21
1UA94	
1UA95	
1UB18	
1UB19	
1UDW9	
1UDX1	
1VTY9	
1VUA1	
1WJF3	Socket Cap 2 In ABS Hub 180 Deg F
1X976	
1X977	
1XLX8	FLOW METER, 1XLX8, GRAINGER, FLOWMETER, VARIABLE AREA MAX. PRESSURE 100 PSI, CONNECTION SIZE (IN.) 1 1/2 FNPT, MAX. TEMP. 150 F, HOUSING MATERIAL ACRYLIC, FLOW RANGE @ GPM OF WATER 5-50 BRAND : KEY INSTRUMENTS
1XRB8	
1XRZ4	
1Z318	TOOL, CARBIDE BUR, GRAINGER #1Z318, 1/4"
1ZE24	
1ZGE8	
2 DDH3	
2.23/4W X 5.1/2 IN H	CLC CELL PHONE
2000010110	Safety-Approved Flashlight, Xenon, ORANGE
20C899	
20J950	Door Louver Finger Guard, Opening Height: 83", Material: Vinyl, Agency; Compliance: UL10C, Includes Fasteners
20X2225 V-BELT	
20Y003	DEWALT Extension Ladder, Fiberglass, 32 ft., IA (Deck). LADDER, EXTENSION, FIBERGLASS, 32 FT Extension Ladder, Material Fiberglass, Extended Ladder Height 32 ft., Ladder Height 36 ft., ANSI Type IA, Load Capacity 300 lb., Adjustable Increments 12 In., Outside Shoe Base Width 17-1/16 In., Rail Type Non Conductive, Shoe Design Aluminum/Rubber
21795 4C448A (BLOWER POLE)	FAN MOTOR W/BLOWER 15V 50/60HZ 1PH 1/15HP 2.9A/3.7A 1530RPM
21YC21	AMERIC Conf Space Blwr/Exhstr, Air Driven, 12 in (Deck). BLOWER, AIR DRIVEN, 1-1/2HP, 3000RPM Confined Space Blower/Exhauster, Air Driven, 1-1/2 HP, Duct Dia. 12 In, Material Polyethylene, Blower/Fan Speed 3000 rpm, Maximum Flow in Free Air 2063 cfm, Inlet Connection 3/8 In. Male QD Fitting, Max. Inlet Pressure 100 psi, Air Consumption 38 cfm, Standards UL, C-UL, OSHA, Color Blue, Length 17 In., Width 14 In., Height 21 In

Продукт	Описание
21YC32	AMERIC Statically Conductive Duct, 12 in x 25 ft (Deck) DUCT, CONDUCTIVE, STATICALLY, 12 IN, 25 FT Statically Conductive Duct, Diameter 12 In., Length 25 ft., Construction Polyester, Color Black, For Use With Mfr. No. VAF3000A. VAF3000B, VAF3000P, Standards UL-94-VO, Includes Quick Connect, (2) Cuffs, Ground Wire.
22C737	
2CB34 ALTERNATIVE	
2DA93 ALTERNATIVE	
2DDG3	
2DDH3	
2DDH6	
2DPD9	CONNECTOR, NYLON CORD, 1 IN CORD CONNECTOR, NPT TYPE, STRAIGHT AND LOW PROFILE, COLOR: BLACK, CORD DIA: 0.59-1.00 IN, LENGTH: 2.41 IN, CONDUIT SIZE: 1 IN, MIN THROAT DIA: 0.59 IN, NYLON.
2DPE4	CONNECTOR, NYLON CORD, 1/2 IN CORD CONNECTOR, NPT TYPE, STRAIGHT AND LOW PROFILE, COLOR: BLACK, CORD DIA: 0.17-0.45 IN, LENGTH: 1.70 IN, CONDUIT SIZE: 1/2 IN, MIN THROAT DIA: 0.17 IN, NYLON.
2DPE6	CONNECTOR, NYLON CORD, 3/4 IN CORD CONNECTOR, NPT TYPE, STRAIGHT AND LOW PROFILE, COLOR: BLACK, CORD DIA: 0.45-0.71 IN, LENGTH: 2.00 IN, CONDUIT SIZE: 3/4 IN, MIN THROAT DIA: 0.45 IN, NYLON.
2DZG6	LOCKNUT, CORD CONNECTOR, 1/2 IN LOCKNUT, CORD CONNECTOR, NON-METALLIC, NYLON, HUB SIZE: 1/2 IN.
2DZG7	LOCKNUT, CORD CONNECTOR, 3/4 IN LOCKNUT, CORD CONNECTOR, NON-METALLIC, NYLON, HUB SIZE: 3/4 IN.
2DZG8	LOCKNUT, CORD CONNECTOR, 1 IN LOCKNUT, CORD CONNECTOR, NON-METALLIC, NYLON, HUB SIZE: 1 IN.
2EJX1	GRINDING WHEEL F/DRILL DOCTOR, 180 GRIT,
2FE61	
2G592	
2HAP6	
2HLG3	
2HLG9	
2NXA5	
2TVG7	
2TVR1	
2TVU6	
2TVX1	
2V706	
2W282	
2WZV7	
2WZV8	
2XKD2	
2XY23	SHACKLE, ANCHOR, SIZE: 3/8 IN SHACKLE, ANCHOR, PIN STYLE SCREW PIN, WIDTH BETWEEN EYES: 21/32 IN, PIN DIA: 7/16 IN, BODY SIZE: 3/8 IN, BODY AND PIN MATERIAL: FORGED STEEL, GALVANIZED, ASTM A-153, WORKING LOAD LIMIT: 2000 LBS.
2XY34	SHACKLE, ANCHOR, SIZE: 3/16 IN SHACKLE, ANCHOR, PIN STYLE SCREW PIN, WIDTH BETWEEN EYES: 3/8 IN, PIN DIA: 1/4 IN, BODY SIZE: 3/16 IN, BODY AND PIN MATERIAL: ALLOY STEEL, ASTM A-153, WORKING LOAD LIMIT: 1000 LBS.
2XY38	SHACKLE, ANCHOR, SIZE: 7/16 IN SHACKLE, ANCHOR, PIN STYLE SCREW PIN, WIDTH BETWEEN EYES: 23/32 IN, PIN DIA: 1/2 IN, BODY SIZE: 7/16 IN, BODY AND PIN MATERIAL: ALLOY STEEL, GALVANIZED, ASTM A-153, WORKING LOAD LIMIT: 5200 LBS.

Продукт	Описание
2XY42	SHACKLE, ANCHOR, SIZE: 3/4 IN SHACKLE, ANCHOR, PIN STYLE SCREW PIN, WIDTH BETWEEN EYES: 1 1/4 IN, PIN DIA: .7/8 IN, BODY SIZE: 3/4 IN, BODY AND PIN MATERIAL: ALLOY STEEL, GALVANIZED, ASTM A-153, WORKING LOAD LIMIT: 14000 LBS.
2YNL6	desiccant dryer
2YNL7	desiccant dryer
2ZPN9	
2ZUY8	
32J054	
34D667	
35T090	
36T992	Air Impact Wrench (plant). WRENCH,AIR IMPACT,IN 3/8INCH,6500RPM Air Impact Wrench,Industrial Duty, Standard Anvil,Average CFM@15 second Run time 9,5. CFM@Full Load 38, Free speed 6500 rpm,Dual Retainer type, pistol grip style,air inlet 3/8 inch
38N842	
3-8SN	
3A493	
3A594	SET, HEX KEY, 3A594,GRAINGER SET, HEX KEY, BALL END, MEASUREMENT TYPE SAE,ARM TYPE LONG, NUMBER OF PIECES 13, ARM LENGTH 2.80 TO 6.80 IN, SIZES INCLUDED0.050, 1/16, 5/64,3/32, 7/64, 1/8, 9/64, 5/32,3/16, 7/32, 1/4, 5/16, 3/8 IN, BLADEMATERIAL ALLOY STEEL,HANDLE TYPE L-SHAPED,MEETS/EXCEEDS ANSI B18.3 AND FEDERAL SPECIFICATION GGG-K-275D, INCLUDES MOLDED PLASTIC HOLDER
3GY61	Adj Hook Spanner Wrench,220 to 324mm Cap. (Plant) WRENCH,SPANNER HOOK,ADJUSTABLE,220-324MM Adjustable hook spanner wrench, Capacity 220 to 324mm, Length 650mm, Thickness 19mm, Material Alloy steel, Finish Chrome
3HAP9	
3HME1	PRESSURE RELIEF VALVE,3HME1, GRAINGER PRESSURE RELIEF VALVE, INLET/OUTLET 1 1/2 IN, FNPTCONNECTION MATERIAL OF CONSTRUCTION PVC, SET PRESSURE RANGE 5 TO 75,DISC MATERIAL PVC, SPRING MATERIAL COATED S/S, SEAT MATERIAL
3KG83 / 5320-0 cannot be exportet von USA	
3LJY4	
3LK75	
3LP22	
3LR85	Reduction of 1 ½ to ¾ inch
3LX40	adapter male 2 In
3LX83 (pack of 25)	Safety Clip
3LZ03 (pack of 50)	Washer
3MC05	
3PXL6	
3R181 J194	
3R408	SET, ADJUSTABLE WRENCH,3R408, GRAINGER SET, ADJUSTABLE WRENCH,NUMBER OF PIECES 3, JAWCAPACITY 1-1/8, 1-5/16, 1-1/2 IN, OVERALL LENGTH 8,10, 12 IN, MATERIALDROP-FORGED AND HEAT TREATED ALLOY STEEL, SATIN CHROME FINISH, PLAIN GRIP HANDLE
3YU40	
453	kit for knives
4A499	WRENCH, PIPE, STRAIGHT, PIPE, STRAIGHT, 14IN LENGTH, ALUMINUM
4A974	

Продукт	Описание
4CR44	SET, TONGUE/GROOVE PLIER,4CR44, GRAINGR SET, TONGUE/GROOVE PLIER,NUMBER OF PIECES 2, MAXIMUM JAW OPENING 1 1/2,7/8 INCHES, JAW TYPESTRAIGHT/STRAIGHT,LENGTH 9 1/2, 6 1/2 IN
4CX15	RIDGID Water Jetter, 1750 PSI (Deck). JETTER,WATER DRAIN CLEANING,2HP,SET Water Jetter Drain Cleaning, 2 HP, Includes (4CW98) 1/4 In x 110 Ft Jet Hose, Cart With Hose Reel, 115 VAC, 17 Amp Motor, Duplex Plunger Pump, For Blasting Through Sludge, Soap and Grease Blockages, Power Scrubs Line as Hose is Pulled Back
4DE71 REPLACED BY 6YTH1	
4DHT5	Check Valve - Stainless, 1/8" Female X Male
4DHT7	Check Valve - Stainless, 1/8" NPT, Male x Female
4EA94	
4F663	
4F663	
4F664	
4F664	
4FPU7	
4FY19 (grainger p/n) = N075UAU10GR (Fill-Rite)	Nozzle
4FY20	
4KME6	
4KP25	
4KYN7	
4NFW6	
4NU55	
4NV39	Adjustable Wrench Locking
4PCY7	Ideal, Data / Video Kit 14 Pieces, Grainger Item: 4PCY7, Mfr Model: 33-917, UNSPSC# 27113201. (I&E) TOOL,DATA/VIDEO KIT,14PCS Data/Video Kit, Number of Pieces 14, Storage Type Large Mouth Tool Bag, Includes Crimpmaster Tool for RJ-45 Modular Plugs, OmniSeal Pro XL Compression Tool, VDV Multi-Media Tester, Coax Connector Tool, Electricians Scissors, 110/66 Blade, Probe Pic/Spudger, Punchmaster Punch Down Tool w/110 Blade, 7-in-1 Twist-a-Nut Screwdriver/Nutdriver, Data-T Cutter, UTP/STP Cable Stripper, Coax Stripper, Amplifier Probe.
4RP93	
4RP94	
4UR44	
4VLX2	EXTRACTOR SET: MATERIAL METAL TYPE CORKSCREW CONTAINER PLASTIC CASE,NUMBER OF PIECES 9,PACKING EXTRACTOR SET A, CORKSCREW, PALMETTO PACKING,MFR. MODEL # 1116
4WZC4	
4WZC5	
4WZH1	
4WZH2	
4YF48	HEAT SHRINK KIT
4YVE6	20 x 24 x 2 High Performance Mini-Pleated filter MERV 14
4ZH66	
4ZK44	
5D932	
5DFT8	

Продукт	Описание
5DV76	
5HYD1	AXE, PICK HEAD FIRE, CUTTING EDGE 4 3/4"IN, HEAD WEIGHT 6 LB, OVERALL LENGTH 36 IN, HANDLE 36 IN, FIBERGLASS HANDLE
5JDH4	
5JDK4	
5JDK9	Acme Flange Overall Diametre 4.94 In
5LJ02	
5LL68	SET, SCREWDRIVER. 5LL68, GRAINGER SET, SCREWDRIVER, NUMBER OF PIECES 7, CUSHION GRIP
5MM87	Mop Handle, Length 60 Inches, Rust Resistant Steel Spring Lever Head Design, 1 1/8 Inch Diameter Wood Handle, Swivel End Cap
5PDK5	PERFORATED SHEET, 5PDK5, GRAINGER PERFORATED SHEET, SS, 40X36, 16 GA, 0.125 DIA, RND MATERIAL: STAINLESS STEEL, FINISH: 2B, ALLOY TYPE: 304, TEMPER: ANNEALED, LENGTH: 40", WIDTH: 36", THICKNESS: 0.060" (1.524 MM), GAUGE: 16, HOLE DIAMETER: 0.125", HOLE SHAPE: ROUND, HOLE PATTERN: STAGGERED, CENTER SPACING: 3/16", OPEN AREA: 40%, LENGTH TOLERANCE: +/- 0.125", WIDTH TOLERANCE: +/- 0.125", THICKNESS TOLERANCE: +/- 0.003", TYPICAL HARDNESS: B90, HARDNESS SCALE: ROCKWELL, TENSILE STRENGTH: 85, YIELD 5PDK5 GNG 5.00 Units STRENGTH: 35
5PDL0	PERFORATED SHEET, 5PDL0, GRAINGER PERFORATED SHEET, SS, 40X36, 18 GA, 0.094 DIA MATERIAL: STAINLESS STEEL, FINISH: 2B, ALLOY TYPE: 304, TEMPER: ANNEALED, LENGTH: 40", WIDTH: 36", THICKNESS: 0.048" (1.2192 MM), GAUGE: 18, HOLE DIAMETER: 0.094", HOLE SHAPE: ROUND, HOLE PATTERN: STAGGERED, CENTER SPACING: 5/32", OPEN AREA: 33%, LENGTH TOLERANCE: +/- 0.125", WIDTH TOLERANCE: +/- 0.125", THICKNESS TOLERANCE: +/- 0.003", TYPICAL HARDNESS: B90, HARDNESS SCALE: ROCKWELL, TENSILE STRENGTH: 85, YIELD STRENGTH: 35
5PNT9	
5PPX6	
5PPX9	
5RGR8	
5RHR6	
5T536	3/4 "Air Impact Wrench Snap on. (Deck) WRENCH, AIR IMPACT, 3/4" DRIVE Impact Wrench, Air, Super Duty, 3/4" Drive ; Lightweight composite housing with aluminum nose ; 3 position thumb operated forward/reverse lever ; Bottom handle exhaust ; Twin hammer mechanism ; 1 Year Limited Warranty ; EU/CE—DE, ES, FR, IT, GB, NL
5TMZ1	
5UGU6	
5UGU7	
5XC30	
5XC31	
5YRHO	
5Z768	Vacuum filter generator
5ZPL8	
5ZPL8	
601026-75 1	OSE: AIR, SIZE 3/4 IN MATERIAL NA, CONNECTION NPT RATING MAX 250 PSI, TYPE AIR HOSE, AIR HOSE ASSEMBLY, REELCRAFT 3/4" ID, 75FT, 250PSI WITH FITTING NPT 3/4
6BA82	
6CA92	
6EY41	
6FA33	
6FAW4	

Продукт	Описание
6FB21	
6FY88	
6GDP5	AXE, CAMPERS, SINGLE BIT AXE, CAMPERS SINGLE BIT, CUTTING EDGE (IN.) 3-1/4, HARDENED STEEL HEAD MATERIAL, HEAD WEIGHT (OZ.) 22, HEAD WEIGHT (LB.) 1-3/8, OVERALL LENGTH (IN.) 14, HANDLE AXE, HANDLE MATERIAL FIBERGLASS W/ GRIP, 2-1/4 FACE, MEETS/EXCEEDS ANSI STANDARDS
6GDV5	Wheeler-Rex Hydrostatic Test Pump, Electric, 1/2 Hp
6GDV7	Wheeler-Rex Test Pump, Electric, Twin Piston 1 Hp
6JLL4	
6KHT0	
6LL72	
6MP47	(Hose,Metal,4 X 9 In Manufacturer No.: G400PF090 Origin: US Harm Code: 8307103000 Hazardous Material: N ECCN:EAR99 NAFTA Qualified: Y)
6PB92	SHOWERHEAD, 6PB92, GRAINGER SHOWERHEAD, WALL MOUNT,COLOR/FINISH CHROME PLATED, MATERIAL OF CONSTRUCTION PLASTIC, CONNECTION 1/2 MIPS IN,MAX. FLOW 2.5 GPM, FEATURES FIVE SPRAY SETTINGS, EXTENDED RUBBER NOZZLE
6RKL8	
6RKP9	
6RKRO	
6RKV0	
6TFG2	
6W461	PUMP: HAND, HIGH FORCE HYDRAULIC, ENERPAC P-142 PUMP: HAND, HIGH FORCE HYDRAULIC PUMP, SPEED: TWO MAX. PSI 1ST/2ND STAGE: 200/10,000 DISP. PER STROKE 1ST/2ND STAGE: 0.221/0.055 RESERVOIR CAPACITY CU.IN: 20 PORT (NPT): 1/4" ENERPAC MODEL P-142 ,DIMENSION: 13-1/4"L, 3-3/4"W, 5-15/16"H
6WA95	Grease Gun, Type Lever, 34 Strokes for 1 Oz Output, Length 21 3/4 In, Nozzle Type Rigid Pipe, Nozzle Extension 6 In, Max Operating PSI6000, Capacity For 16 Oz Bulk or 14 1/2 Oz Cartridge
6XFX7	WIRE ROPE AND CABLE CUTTER NON-CONDUCTIVE, OVERALL LENGTH (IN.) 35, CUTTING CAPACITY /MATERIAL 7/16"" DIA. WIRE ROPE, 9/16"" DIA. CABLE, JAW LENGTH (IN.) 1-5/8, JAW WIDTH (IN.) 0.5625, JAW MATERIAL HIGH GRADE TOOL STEEL, BLADE TYPE WIRE ROPE/CABLE CUTTER, FIBERGLASS HANDLE, HANDLE LENGTH (IN.) 25-1/2, VOLTAGE RATING 1000, FOR CUTTING WIRE ROPE AND CABLE
6YB33	DRILL BIT SHARPNER, MODEL DRILL DOCTOR 118 TO 135 GEG,
6YH34	
6YTH1	
7D820 IS DISCONTINUED AND NO INVENTORY EXISTS, THE ALTERNATIVE ITEM IS 1UDW9	
7D821 IS DISCONTINUED AND NO INVENTORY EXISTS, THE ALTERNATIVE ITEM IS 1UDX1	
8M725	
9007C54	heavy-Duty Limit Switch top Plunger Type spring return SPDT Square D
9GD34	Magnetic Pickup Tool
9HV62	
9LHH4	
9UDU8	Small White Plastic Chain Type 9UDU8 with each Linked 3 Thickness 6 mm, Lenght 2500 mm, Kinked Dimension 38x20 mm

Продукт	Описание
A245	safety plug
A39 2D 833	ABRASIVE POINT
A41 2D 835	ABRASIVE POINT
AM 410	seal kit for motor
AM12	COUPLER: QUICK DISCONNECT SIZE 1 INCH, CONNECTION NPT MATERIAL MALLEABLE IRON, TYPE MALE COUPLER, MALE COUPLER 1 INCH FOR AIR HOSE
AM13	COUPLER: QUICK DISCONNECT SIZE 1 INCH, CONNECTION NPT MATERIAL MALLEABLE IRON, TYPE FEMALE AIR COUPLER, FEMALE COUPLER 1 INCH FOR AIR HOSE
APCG20010	Pipe 2 In 10 Ft ABS
AT123AL	WRENCH: IMPACT, AIR, 1/2 IN DRIVE(25-300), SNAP ON AT123AL SNAP ON AT123AL, IMPACT WRENCH, AIR, HEAVY DUTY, LONG ANVIL, 1/2" DRIVE (25-300 FT. LBS.)
C28-04-FLGO	REGULATOR: FILTER, TYPE AIR INLET PRESSURE MAX 250 PSI BODY MATERIAL METAL, OUTLET PRESSURE 0 - 125 PSI, SIZE/CONNECTION 3/4 IN, IAR REGULATOR FILTER AND LUBE, WILKERSON, 3/4" NPT, MAX 250PSI
CONNECTER STRAIGHT JIC-BSPP FEMALE OD:1"	
CONNECTER STRAIGHT JIC-BSPP MALE WITH ELASTOMERIC SEAL OD:1"	
CONNECTER STRAIGHT JIC-BSPP MALE+O-RING+RETANING RING SEAL OD:1"	
CONNECTER STRAIGHT SWIVEL FEMALE JIC-BSPP SOLID MALE O-RINGBOSS OD:1"	
ELBOW CONNECTER ADJUSTABLE JIC-BSPP MALE+O-RING+RETANING RING SEAL OD:1"	
ELBOW CONNECTER LONG ADJUSTABLE JIC-BSPP MALE+O-RING+RETANING RING SEAL OD:1"	
ELBOW UNION 45 JIC-JIC SWIVEL FEMALE OD:1"	
ELBOW UNION 90 JIC-JIC MALE OD:1"	
ELBOW UNION 90 JIC-JIC SWIVEL FEMAL OD:1"	
HOSE RUBBER FLEXIBLE ID:1" TYPE:4S EN 856-4SH/25 MAX.PRESSURE:350BAR WITH STRAIGHT FEMALE FITTINGS S	

Продукт	Описание
HOSE RUBBER FLEXIBLE ID:1.5" TYPE:4S EN 856-4SH/25 MAX.PRESSURE:350BAR WITH STRAIGHT FEMALE FITTINGS	
HP1-1/2	GRAINGER SUBMERSIBLE SEWAGE PUMP, 1,5 HP, 230V, 18 FT (GOULDS WATER TECHNOLOGY), ItemSubmersible Sewage Pump · Pump TypeManual · HP1-1/2 · Base MaterialCast Iron · HousingCast Iron · Top MaterialCast Iron · Impeller MaterialCast Iron · Shaft MaterialSilicon Carbide · Voltage230 · Phase3 · Amps9.6 · Height19" · Dia.12-1/2" · Cord Length20 ft. · Discharge NPT2" · Max. Dia. Solids2"
HP2-1/2	GRAINGER CENTRIFUGAL PUMP, AIR OPERATED, 3 INCH (WARREN-RUPP),ItemCentrifugal Pump · TypeAir Operated, Submersible · HP2-1/2 · Discharge Port (In.)3 · Air Inlet Pressure (PSI)80 · GPM of Water @ 5 Ft. of Head300 · GPM of Water @ 10 Ft. of Head275 · GPM of Water @ 15 Ft. of Head240 · GPM of Water @ 20 Ft. of Head210 · GPM of Water @ 25 Ft. of Head175 · GPM of Water @ 30 Ft. of Head150 · GPM of Water @ 35 Ft. of Head125
IDEAL GROUND SCREW, 10-32, GREEN, PK100 ,10K067	
NB16B BOSTON GEAR obsolete 2H097 PWC9 replacement 10D457	Boston gear
P/N: 4LZH3	WIRE CUTTER, 8 1/2 INCHES, CENTER CUT HARD METALS TO 5/32 INCHES
ROPE:3-1IN;10IN CIRC	CYLINDER, REFRIGERANT RECOVERY; 50 LB TANK, 1320.6 IN3 VOLUME, 400 PSI, INCLUDES 3/4 IN PLUG
S-02501	THIMBLE,GALV STEEL,FOR 3-1/4IN DIA FIBER ROPE 10IN ROPE CIRCUMFERENCE, HIGH STRENGTH GALVANIZED STEEL
S-02502	Belt Jelco
SAAKGK	Belt Jelco
SM-5000	Rescue Hook, Length 6 ft., Yellow, Material Fiberglass with Aluminum Bronze Alloy Head, Includes 18 In. Opening, Standards ASTM F711
SPLICE 8-12 AWG	SHOWER VALVE, 6MPE9, GRAINGER SHOWER VALVE,THERMOSTATIC/PRESSURE BALANCE, HANDLE TYPE LEVER, HANDLE FINISH POLISHED CHROME, COLOR/FINISH POLISHED CHROME, MATERIAL OF CONSTRUCTION BRASS, ZINC AND PLASTIC, CONNECTION (IN.) 1/2, MAX. FLOW 2.5 GPM, FEATURES ANTI-SCALD PROTECTION DOWN TO 1.5 GPM, ADA COMPLIANT YES, STANDARDS ASSE 1016 <(>&<)> ASME A112.18.1/CSA B125.1, INCLUDES ROUGH-IN TEMPLATE MODEL # SM-5000
SPLICE 8-16 AWG	
SS-FM4SL4SL4-36	HOSE: FLEXIBLE, METAL, 1/4 IN SWAGELOK SS-FM4SL4SL4-36 HOSE: FLEXIBLE, METAL, 1/4 IN, HIGH PRESSURE TYPE, 316SST, HOSE SERIES FM4, END CONNECTION 1/4 IN, LENGTH 36 IN, TUBE OD 1/4 IN, SWAGELOK SS-FM4SL4SL4-36
UNION STRAIGHT JIC-JIC MALE OD:1"	
VS-1001-ADA	
W185 4F 782	
W200 2D 887	ABRASIVE POINT
W2047 2D 888	ABRASIVE POINT
XPA1700	ABRASIVE POINT
907GEL(12Z329)	Length, Pitch : 1700 MM Length, Inside : 1655 MM,Height : 10 MM,Length, Outside : 1718 MM Material : NEOPRENE FILLER AND COVER
5X609	Seat Cushion,Anti-Vibration,18x16 In. Manufacturer No.: 907GEL Origin: US Harm Code: 6307909889 Hazardous Material: N ECCN:EAR99 NAFTA Qualified: N
4YRW2	Visor, Safety Face Shield, Clear, Heavy-duty, Scratch Resistant, 8X15.5X0.055 IN
	Sealant, Pipe Multi-Purpose, 32 Oz Can, Color Yellow, Temp Range -50 to 400 F, Gas Pressure Range

Продукт	Описание
5PKJ2	Hopper Caster Kit, 4800lb, 6 IN Dia: Start (Dayton)
5E532	Cement, 8 Oz, Amber, PVC, CPVC, ABS, WW90802
WW91402	Cleaner, PVC, CPVC, ABS, Clear, 8 Oz Can
WW91202	Primer, 8 Oz, Purple for use with PVC & CPVC & Fitting
1ZKY1 WESTWARD 1100 Lb, 9 - 24 3/4 In	Transmission Jack
5ML72 WESTWARD 1000 Lbs	Hydraulic Transmission Lift
5JG41	Dispenser Long roll
5JG36	Shop towel roll, white 800feet length
13Y352	Cloth Rag
1RYG2	O-Ring Assortment
5ZLT9	COPPER WASHER I.D.6MM-O.D.10MM-THK1MM,IN PACKAGE WITH 25WASHER EACH
5ZLU0	Copper Washer I.D.8mm-O.D.12MM-THK1MM,IN PACKAGE WITH 25WASHER EACH
5ZLU1	Copper Washer I.D.10MM-O.D.14MM-THK1MM,IN PACKAGE WITH 25WASHER EACH
5ZLU2	Copper Washer I.D.10MM-O.D.16MM-THK1MM,IN PACKAGE WITH 25WASHER EACH
5ZLU3	Copper Washer I.D.12MM-O.D.16MM-THK1,5MM,IN PACKAGE WITH 25WASHER EACH
5ZLU4	Copper Washer I.D.12MM-O.D.18MM-THK1,5MM,IN PACKAGE WITH 25WASHER EACH
5ZLU5	Copper Washer I.D.14MM-O.D.20MM-THK1,5MM,IN PACKAGE WITH 25WASHER EACH
5ZLU6	Copper Washer I.D.16MM-O.D.20MM-THK1,5,IN PACKAGE WITH 25WASHER EACH
5ZLU7	Copper WASHER i.d.18MM-O.D.24MM-THK1,5,IN PACKAGE WITH 25WASHER EACH
5ZLU8	Copper Washer I.D20MM-O.D.26MM-THK1,5MM,IN PACKAGE WITH 25WASHER EACH
3KUX1	Electrical Tape Width 3/4, IN PACKAGE WITH 10 ROLLS EACH
29GA12	Left Elbow Battery terminal 1/0GA Black, IN PACKAGE WITH 5 CLAMPS EACH
29GA04	Right Elbow Battery Terminal 1/0GA Black,IN PACKAGE WITH 5 CLAMPS EACH
GLC-01613	Bottle Cleaned, 2 oz, 53-400, PK 24
239553	Glass Bottle, 4 oz., Clear, PK 24
W209912	Plastic Jar, 30mL, PK 72
W209915	Plastic Jar, 250mL, PK 36
6930-0000	Spatula, Sterile, Polystyrene, PK100
36906-2008	Sterile Sampling Scoop, 250mL/8oz.
36944-0000	Sampler Spoon, Sterile, 4.93mL/1 tsp, PK200
P31206	
LB132318	Label, 7/8 In. H, 2-7/8 In. W, PK500
1VNG6	
1VNG7	
1VNG8	
40J770	Kit cable tie assortment
2DPK6	Pump
5X424	
3520-14.00K	Helical Thread Repair Kit
5FZW7	
JLAN15LBSSCAR	Tool Lanyard
4YF48	Heat Shrink Tubing Kit, Black, 74 Pc
5xge3	USB HUB
4WZV2	BUILDING WIRE, BARE COPPER,

Продукт	Описание
2KXN2	GROUND ROD CLAMP
2KXN1	GROUND ROD KIT
25AR86	SCREWDRIVER BIT SET
A53EA12,Item:4EUD4	
9/16-18 UNF 85248802DRS05	
2A096	GOODWRAPPERS STRETCH WRAP
09-04-829	COMBINATION DRIVE SOCKET SET
5C602	PLIER SET
4LB18	MAGNETIC BASE AND DIAL INDICATOR SET
4LA81	DIAL CALIPER (MITUTOYU)
10600	Crimp Connector Kit
4184-53	Leak Detector
4LZH2	Refrigerant Recovery Cylinder
18975	Vacuum/Charge and Core Removal Tool
4PDJ3	1/4 In Valve Core
K22P-TU	Welding and Cutting Outfit
BCUP5-125-01T	Brazing Filler Metals
5PWF9	Refrigerant Scale
45DV24	Mine Spray Hose
3TFP5	Screw-In CFL
EK16	Ground Clamp
RAINBOW 2	Tape
16W274	Straight Blade Connector
16W275	Straight Blade Plug
4215	Yellow Hot Switch Stick
GD5X125-O/B	Cable Protector
CP2X325-Y/O	Cable Protector
90847	Breaker Lockout
90853	Breaker Lockout
31-425	Paint Mixer
2CYX8	Lighter
1VAF9	Carbon Steel Wire Scratch Brush
10C508 (grainger p/n) = TSHF-N-575 (COXREELS)	Hose Reel
2RB96 (grainger p/n) = 700F3135 (Fill-Rite)	Fuel Hose
24UY36 (grainger p/n) = S075H1314 (Fill-Rite)	Hose Swivel
5P574	Reducer
45PV72	Grease Gun Kit
5ZN11	Synthetic Grease
39M982 (1x200)	Disposable Wipes
44A390 Model: NP-17	
P/N: 3XK04 Type: W5025	Noninsulated Flexible Duct
3LX97	Coupler
3LX99	Coupler
3LX98	Coupler

Продукт	Описание
3LZ01	Coupler
3LX91	Coupler
3LX92	Coupler
3LX86	Coupler
3LX95	Coupler
3LX96	Coupler
3LX94	Coupler
3LX89	
3LX90	
3LX97.	Coupler
3LX86.	Coupler
5Z332	
3JT78	
4YLR7 obsolete/alternative 44ZF61	Petro hose
3LX24	
3LX10	
3LX16	
3LX12	
44ZF61	
38ZW44 (pack 1x5)	Hex Head Cap Screw
35YU92 (pack 1x50)	Fender Washers
45NZ74 (pack 1x25)	Hex Nut
4XT09 (pack 1x100)	Disposable Gloves
3XL12	Direct replacement Water Cooler controls
4X258	
4HA34	Pump,drum,hand operated,rotary
3LZ03 (pack x50)	
37450	cardboard sorting boxes, small
37465	Cardboard sorting boxes, large
SKF36	Cardboard roll
6FY82 - 10pcs per package	Conical Washers
6FY84 - 10pcs per package	Conical Washers
6FY64 - 5pcs per package	Conical Washers
6FY88	Conical Washers,M20
2NNZ7	
3MRK2 (pack x50)	
19NF96 - AEROFLEX	
19NF98 - AEROFLEX	
4VZR6 - K-FLEX USA	
45AR72 - K-FLEX USA	
U51411.043.0002 (pack x25)	
NAS1149-C0763R (pack x25)	
4XR60 (50 ft/15 m)	Air Hose

Продукт	Описание
2XB82 / GF15WLA obsolete/replacement	
39EA20 / GFRST15W	
39EA20 / GFRST15W	
3KH39 / 5101-0	
EE1806NFX12	
EE2603DTX10	
EE2802NFX6	
30C522	Voltage Converter
4VLX3 / 1117	
5A293	
A31	Compressor belt
4L480	
6A141	
6X569	
6A139	
3GWW6	
3VU41	
6A123	
3X703	
6A158	
6A126	
6L276	
13W529	
3GXC4	
6L278	
Mobilgrease 28	
polirex EM	
36J158A	Power first cable ties
36J150 (pack x100)	
2MYR1	RECTANGULAR RUBBER STUMP
4GNZ2	
4GPG4	
CP2622	Air Screwdriver,Industrial
20RV50 / 60440108706	
20RV51 / 60440108722	
4XP67	
6JD87 / 32-000230-0000	Eye Wash Station,Green
30UK56	
4WRL8	
5CRU5	
6RNA8 (pack x50)	
305-U / 3CWX4	
3JT82	MULTIPURPOSE HOSE
6CLW1	Fire Hose Nozzle
41UP37	
5ZV86	Insulating Blanket 1 m x 1 m
4BA80 / 150360-75	

Продукт	Описание
4BV10 / 155387-75 (pack x20)	