

Tognella



Tognella - производит товары высокого качества, и имеет безупречную репутацию . Благодаря тому, что наша компания напрямую сотрудничает с фирмой-производителем, Вы сможете быстро получить товар по самой низкой цене. Если нужного товара, нет в списке, сообщите нам, и мы поможем Вам его найти.

ТОВАРЫ БРЕНДА

Продукт	Описание
100041318 FT 257/2-1/4	valve
240-010-01250 (FT257-2-100)	FLOW REGULATOR FOR LUBE OIL SYSTEM
240-030-01200 FT257-5-34	FLOR CHECK VALVE FOR ACTUATOR , MAXIMUM WORKING PRESSURE: 400 BAR
240-030-01200 FT257-5-34	for actuator TYPE: 34 CONNECTION: 3/4" MAXIMUM WORKING PRESSURE: 400 BAR
240-080-01000	
240-080-01000 FT290-14	Manometerabsperrentil 1/4" AG Stahl max. 400bar bei Bedarf zugehörige Kontermutter (extra bestellen) FT202-2 240-Rohrleitungsventile T
240-080-01050 FT290-01-14	
99999 (OSL- FT2257/6-12)	Check Valve
FPE 1/4 IN G	
FPEA 1/4 IN G	
FT 1253/5	
FT 221/1 - 12	
FT 221/1#12	
FT 2257/7-100	
FT 2257/7-12	
FT 2257/7-14	
FT 2257/7-34	
FT 2257/7-38	
FT 257/5	
FT 257/5 - 1/2	
FT257-5-38	
FT 257/6	Check valve
Z240-00005-99999	Rückschlagventil
FT 257/6 - IG 1/2	
FT 257/6 - IG 3/4	
FT257/6-34	Rückschlagventil
FT 260/6#100	
FT 291-01	
FT1237-2-01-18	

Продукт	Описание
FT2251-2-01-12 NPT	Throttle valve 1/2 "NPT - AISI 316-18/8 max. 210bar - 60l/min. Stainless steel V2A; X10CrNi18-8 IG 1/2 "NPT (tapered)
FT2251-2-01-38 NPT	Throttle valve 3/8 "NPT - AISI 316-18/8 max. 210bar - 30l/min. Stainless steel V2A; X10CrNi18-8 IG 3/8 "NPT (tapered)
FT2257/2-100	
FT2257/2-12	
FT2257/8-14	Double check valve gest.G 1 / 4-1.4401, Txp: 14, Format: controlled, Nominal pressure: max. 400 bar, Thread: G1 / 4 "internal, Temperature: -20 ° C to + 130 ° C, Overall length: 126mm Material: 1.4401
FT2257-2-14	
FT2260/6-100	
FT2260/6-12	
FT2260-6-14	CHECK VALVE, TYPE:INLINE,SINGLE,BALL VALVE SIZE:1/4", PRESSURE RATING:350BAR, CONNECTION TYPE:THREADED NPT FEMALE, BODY MAATERIAL:SS316
FT257-5-34	Drosselrückschlagventil 3/4" Stahl
FT267/2-38	double acting needle control valve
FT267/5-34-V	
FT270/5-38 - 210 BAR	
FT270-5-100	Flow Control
FT290-14	Manometerabsperrventil
OSL-FT2257/2-12	Needle-regulating Material steel, PTFE sealing, connecting sleeves female thread, double acting
Z240-00021-99999 (OSL-FT2257/6/8-12)	(FT2257/6/8-12 Rückschlagventil 1/2" Edelstahl 8 bar Vorspannung Werkstoff 1.4401 (X5CrNiMo17-12-2) AISI 316, (V4A) 240-Rohrleitungsventile T)
Z240-00026-99999 FT287/2-38	Flow control valve
FT257-5-14	Drosselrückschlagventil 1/4" Stahl max. 400bar - 13l/min.
260/6 - 34 GAS BAR 4,5	Rückschlagventil 3/4" - 400 bar Öffnungsdruck 4,5 bar
260/6 - 38 GAS BAR 4,5 (Not available)	
FT2290-14	OSL-FT2290-14
FT252-2-14	Drosselventil
FT257-5-100	Drosselrückschlagventil 1" Stahl
FT257/6-38-10	Rückschlagventil
FT290	Isolation gauge
FT 247/2-Type 18-Viton	
FT1251-2-01-14	
FT1251-2-01-18	
FT1251/2-01 34	
FT1251-2-01-12 (240-040-01150)	
FT267/2-14	
FT1251-2-01-14	
FT1251-2-01-38	
FT1251-5-01-14	
FT1251-5-01-38	

Продукт	Описание
FT290,	GAUGE ISOLATOR
FT257/2-12 - VITON Z240- 00030-99999	
FT1251-2-01-38-V Z240-00069- 99999	
240-050-01200	Drosselventil
FT 29014	Manometerabsperrentil
Drosselventil 3/8" Messing-Viton	
FT257/2-12 - VITON	
IPN-035/E 36/1010	valve
FT1251-2-01-14	ventil
FT1251-5-01-12	
FT267/2-12	240-Rohrleitungsventile T
FT 1251/2-14, Nr 8131008	valve
FT267/5-100	
FT257/6-14	Rückschlagventil
99999	Drosselventil
FT2257/2-18	
FT270-5-14	
FT267/5-38	
FT270-5-34	
FT267/2-34-V	
OSL-FT2299-42	Manometer
FT-291-1/4"	
FT-257/1-1/4"	
FT1251-2-01-38	Drosselventil
FT1251-2-01-12	Drosselventil