

Codan 8024 Food Hose



Codan 8024 - BfR, kap XXI, kat. 2. EU Reg. No.: 1935/2004 & 2023/2006

Blue, smooth, flexible hose with BfR-approved inner rubber layer. For hot and cold beverages, e.g. beer, wine, fruit juice and milk. Inner and outer surfaces resistant to vegetable and animal oils. Certification can be supplied.

It is recommended that new hoses are flushed with 5% soda solution before use. Flushing after use is also recommended.

Normally installed using stainless connectors or hose clamps.

Please contact Codan for further information.

Type nr. 8024

Application: Food / Beverages

Standard Length: 50 metres

Working Temperature: -20°C to 100°C

Inside: NBR

Colour: White

Reinforcement: PVA

Outside: NBR/PVC

Colour: Blue

Standards: BfR, kap XXI, kat. 2. EU Reg. No.: 1935/2004 & 2023/2006

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
6,3	15,0	20	60	60	192	8024006000
9,5	18,5	20	60	74	262	8024010000
12,7	21,6	20	60	86	317	8024013000
15,9	25,1	20	60	100	392	8024016000
19,1	28,6	20	60	114	469	8024019000
25,4	35,6	20	60	142	645	8024025000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.



© Codan Rubber Danmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark
Tel. +45 56 64 64 64 Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com

06/05/2015